# GAMMA GS 10 SLIM SB

ENCLOSED SUBWOOFER



The **GS 10 SLIM SB** is the ready-to-install enclosed subwoofer with the GS 10 SLIM. The sealed enclosure is only 130 mm high and fits in the boot, under covers or behind seats. Both voice coils are wired in series at the factory, giving 4 Ω at the terminal. With the GLADEN ATM module (accessory) it can be upgraded to an active subwoofer.

## MEASURED DATA AND SPECIFICATIONS

### Electrical

| | | | |
|---|---|---|---|
| Impedance at the terminal | Z | 4 | Ω |
| DC resistance | $R_e$ | 3.24 | Ω |
| Power handling RMS | P | 300 | W |
| Power handling max. | $P_{max}$ | 450 | W |

### Enclosure

| | | |
|---|---|---|
| Type | sealed | |
| Subsonic filter 24 dB/oct. | 20 | Hz |

### Installation and construction

| | | |
|---|---|---|
| Driver | GS 10 SLIM | |
| Width | 500 | mm |
| Depth | 380 | mm |
| Height | 130 | mm |
| Height with feet | 157 | mm |
| Connection | round push terminal | |
| Upgrade | ATM module | |
| Covering | grey | |
| Net weight | 9.9 | kg |

## DIMENSIONS

1 terminal · 3 feet · dimensions in mm




- Set the amplifier's subsonic filter to 20 Hz, 24 dB/oct.