C95 II

2-Way Floor Standing Speaker



JAMO® is a trademark of JAMO HOLDING - www.jamo.com – 04/2025- VI
All features and specifications subject to change without notice

Key Features

The C95 II is a 2-way bass-reflex system designed for exceptional detail and balanced, dynamic reproduction.

Hybrid Composition Conical Cone (HCCC) woofer technology provides the stiffness and strength of aluminium or titanium, with the transient response and smoothness of wood fiber, while Long Displacement Surround (LDS) provides cleaner, tighter, and deeper bass.

Paired with the I" silk dome tweeter mated to an Anti-Diffraction Waveguide (ADW) for exceptionally smooth high frequency extension both on-axis and off, the Jamo C95 II floor standing speaker envelops the listener in warm, natural sound throughout the environment.



Anti-Diffraction Waveguide (ADW) & Tweeter Distortion Reduction (TDR)
Refined trebles and flexible positioning in the room.

Aluminium Phase Plug
A hallmark of Jamo's design, smoother frequency response and better power handling in the upper range of the driver's response.

Hybrid Composition Conical Cone (HCCC) & Long Displacement Surround (LDS)
Controlled damping and linearity, resulting in lower distortion and better transient response.

Iconic Design & Magnetic Grilles
Jamo's design language masterfully plays with the tension between angular precision and organic curves - where sharp, geometric cabinet lines would suddenly give way to softly rounded baffle edges, creating a unique visual rhythm.

Available Colours and CMF Options

Black Ash 

JAMO® is a trademark of JAMO HOLDING - www.jamo.com – 04/2025- VI
All features and specifications subject to change without notice

Technical Specifications

Acoustical Features	Type	Floor standing passive loudspeaker 2-way bass-reflex
	Speaker Drivers Configuration & Technologies	• LF : 2 x 152.4 mm (6") woofer HCCC Aluminium Phase Plug LDS technology • HF : 1 x 25.4 mm (1") positive dome tweeter ADW TDR technology
	Bandwidth (+/-3dB)	37 Hz - 24 kHz
	Low-frequency Cut-off (-6dB)	30 Hz
	Sensitivity (2.83V @ 1m)	89 dB
Electrical Features	Power (Rated/Peak)	165 W / 330 W
	Recommended Amplifier Power	> 75 W
	Impedance	6 Ω
	Inputs	Bi-wiring terminal – Chrome plated
Product Main Information	Dimensions H x W x D (mm) H x W x D (inches)	982 x 215 x 317 mm 38.66" x 8.5" x 12.5"
	Included Accessories	Magnetic grilles
	Net Product Weight	20 kg / 44 lbs
	Available Colours	● Black Ash

JAMO® is a trademark of JAMO HOLDING - www.jamo.com – 04/2025- VI
All features and specifications subject to change without notice